

## RFID Privacy Capability Statement for 15693 integrated circuit (chip)

### *Product details for the integrated circuit (chip)*

Manufacturer	
Product commercial reference	
Product type reference (if different from the commercial reference)	
Form completed by (company, if different from the manufacturer)	
Form completed by (person)	
Complies with standard (please indicate the version)	<b>Version (Amd)</b>
ISO/IEC 15693	
ISO/IEC 15693-1	
ISO/IEC 15693-2	
ISO/IEC 15693-3	
ISO/IEC 18000-3 Mode 1	
Center Frequency	MHz
Maximum Data rate (VICC -> VCD)	bits/s
Maximum Data Rate (VCD -> VICC)	bits/s
Proprietary or custom commands supported by the integrated circuit in relation to privacy protection. Please list below	
UID memory size	bits
User memory size	bits

**Privacy capability features supported by the interrogators**

Code	Privacy capability feature supported by the standards	Supported: ✓ box
C-16	Write (Lock) protection	
C-26	Verification using the unique Tag ID <sup>A</sup>	
Additional proprietary features supported by the integrated circuit. Please list below. (eg. Chip selection with random number, reduce read range, ...)		
<sup>A</sup> For ISO/IEC 15693-X the Tag ID is called UID		